

## CLAIMS

Please amend the presently pending claims as follows:

1. (Currently Amended) System for remote control of apparatuses, enabling the interconnection between at least one broker and at least one remote apparatus, said at least one broker carrying out according to the MQIsdp protocol,  
wherein the system associates to said, with at least one ~~of said~~ remote apparatuses, radiocommunication means comprising:, ~~which are external to said at least one of said remote apparatuses and are capable of internally processing a communication protocol implementing API source functions available in a software platform enabling at least one application to be embedded, and~~  
~~wherein said radiocommunication means are provided with a set of specific (API) functions enabling data to be exchanged with at least one server implementing said MQIsdp protocol,~~  
exchanging means for:  
exchanging data between said radiocommunication means and said at least one remote apparatus according to a set of specific API functions;  
exchanging data between said radiocommunication means and said at least one broker according to said MQIsdp protocol;  
interfacing means for interfacing between said set of specific API functions and said MQIsdp protocol,  
so as to enable an interconnection between said at least one broker and said at least one remote apparatus via said radiocommunication means, with the latter also managing at least one application between said at least one broker and without said at least one remote apparatus knowing said MQIsdp protocol.
2. (Currently Amended) System for remote control of apparatuses according to claim 1, wherein

said radiocommunication means include a radiocommunication module, grouping together on a single substrate all of the radiofrequency and baseband data processing means, as well as means for managing said ~~(API)~~ set of specific API functions and said at least one application.

3. (Currently Amended) System for remote control of apparatuses according claim 1, wherein said radiocommunication means integrate said MQIsdp protocol in the form of a library, defining said set of specific ~~(API)~~ API functions.

4. (Previously Presented) System for remote control of apparatuses according to claim 1, wherein at least in a first mode, said radiocommunication means manage only the signalling of a data exchange, with said data being transferred directly from a remote apparatus to a server, or the reverse.

5. (Previously Presented) System for remote control of apparatuses according to claim 1, wherein at least in a second mode, said radiocommunication means manage the signalling of a data exchange and the transfer of said data, with the latter being temporarily stored in at least one buffer storage.

6. (Previously Presented) System for remote control of apparatuses according to claim 5, wherein the size of said at least one buffer storage is parameterable.

7. (Previously Presented) System for remote control of apparatuses according to claim 6, wherein the system operates in said first mode when the size of said at least one buffer storage is 0, and in said second mode if not.

8. (Previously Presented) System for remote control of apparatuses according to claim 1, wherein said set of specific API functions includes functions enabling:

- connection to one of said at least one broker;

- sending of messages;
- receiving of messages;
- configuration of at least one parameter.

9. (Currently Amended) System for remote control of apparatuses according to claim 1, wherein at least some of said specific (API) set of specific API functions are organised so as to be capable of providing at least two operations and/or acting on at least two distinct aspects, according to a predefined parameterization.

10. (Currently Amended) System for remote control of apparatuses according to claim 1, wherein said set of (API) specific API functions includes only 12 functions.

11. (Currently Amended) System for remote control of apparatuses according to claim 1, wherein said set of specific (API) API functions includes an initialisation function restoring default parameters, which must be called at least once before the use of other (API) API functions.

12. (Currently Amended) System for remote control of apparatuses according to claim 1, wherein said set of specific (API) API functions includes a function called when an IP connection has been established.

13. (Previously Presented) System for remote control of apparatuses according to claim 1, wherein the system includes a function of establishing a connection with one of said brokers, making it possible to define parameters of said connection, and a function for disconnecting said connection.

14. (Previously Presented) System for remote control of apparatuses according to claim 13, wherein said function of establishing a connection makes it possible to select a transmission mode from at least two.

15. (Previously Presented) System for remote control of apparatuses according to claim 1, wherein the system includes a function for sending a message to one of said brokers.

16. (Previously Presented) System for remote control of apparatuses according to claim 1, wherein the system includes a function for subscribing to one of said brokers, and a function for unsubscribing to said broker.

17. (Previously Presented) System for remote control of apparatuses according to claim 1, wherein the system includes at least one function for requesting information on at least one aspect of a communication in progress.

18. (Previously Presented) System for remote control of apparatuses according to claim 17, wherein the system includes at least one of the functions belonging to the group including:

- a function for inquiring about the status of a connection;
- a function for inquiring about the status of a given message;
- a function for inquiring about the current size of a queue; and
- a function for inquiring about the space available in a queue.

19. (Previously Presented) System for remote control of apparatuses according to claim 1, wherein the system includes a function for defining the size of a queue.

20. (Currently Amended) Method for remote control of apparatuses, enabling the interconnection between at least one broker and at least one remote apparatus, said at least one broker carrying out according to the MQIsdp protocol,

wherein the method associates to said, with at least one ~~of said~~ remote apparatuses, radiocommunication means comprising: ~~which are external to said at least one of said remote apparatuses and are capable of internally processing a communication~~

~~protocol implementing API source functions available in a software platform enabling at least one application to be embedded,~~  
~~and wherein the method implements, in said radiocommunication means, a set of specific API functions enabling data to be exchanged with at least one broker implementing said MQIsdp protocol,~~  
exchanging means for:  
exchanging data between said radiocommunication means and said at least one remote apparatus according to a set of specific API functions;  
exchanging data between said radiocommunication means and said at least one broker according to said MQIsdp protocol;  
interfacing means for interfacing between said set of specific API functions and said MQIsdp protocol,  
so as to enable an interconnection between said at least one broker and said at least one remote apparatus via said radiocommunication means, ~~with the latter also managing at least one application between said at least one broker and without said remote apparatus knowing said MQIsdp protocol.~~

21. (Currently Amended) A radiocommunication device comprising:

a remote apparatus; and  
radiocommunication means associated with and external to said remote apparatus, ~~the radiocommunication means comprising: for internally processing a communication protocol implementing API source functions available in a software platform enabling at least one application to be embedded, and wherein said radiocommunication means are provided with a set of specific (API) functions enabling data to be exchanged with at least one server implementing an MQIsdp protocol,~~  
exchanging means for:  
exchanging data between said radiocommunication means and said at least

one remote apparatus according to a set of specific API functions;  
exchanging data between said radiocommunication means and said at least  
one broker according to said MQIsdp protocol;  
interfacing means for interfacing between said set of specific API functions and  
said MQIsdp protocol,

so as to enable an interconnection between at least one broker and said remote apparatus via said radiocommunication means, ~~with the latter also managing at least one application between said at least one broker and without~~ said remote apparatus ~~knowing said MQIsdp protocol.~~

22. (Currently Amended) A device comprising:  
a radiocommunication module; and  
radiocommunication means associated with and external to the radiocommunication module, ~~the radiocommunication means comprising: for internally processing a communication protocol implementing API source functions available in a software platform enabling at least one application to be embedded, and wherein said radiocommunication means are provided with a set of specific (API) functions enabling data to be exchanged with at least one server implementing an MQIsdp protocol,~~  
~~exchanging means for:~~  
~~exchanging data between said radiocommunication means and said at least~~  
~~one remote apparatus according to a set of specific API functions;~~  
~~exchanging data between said radiocommunication means and said at least~~  
~~one broker according to said MQIsdp protocol;~~  
~~interfacing means for interfacing between said set of specific API functions and~~  
~~said MQIsdp protocol,~~  
so as to enable an interconnection between at least one broker and said radiocommunication module via said radiocommunication means, ~~with the latter~~

~~also managing at least one application between said at least one broker and without said radiocommunication module knowing said MQIsdp protocol.~~

23. (Cancelled)